



▲ Designate proper finish suffix

◆ Your Delta Faucet hand shower incorporates a backflow protection system that has been tested to be in compliance with ASME A112.18.3, ASME A112.18.1/CSA B125.1. It incorporates two certified check valves in series, which operate independently and are integral, non-serviceable parts of the wand assembly.

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only.

ODELTA:

THREE HOLE ROMAN TUB FAUCET WITH HAND SHOWER TRIM

- Trinsic® Bath Collection
- Single Handle Roman Tub Faucet with Hand Shower
- Three Hole Installation
- Rough-In Kit Must Also be Ordered to Complete Installation

STANDARD SPECIFICATIONS:

- Hand Shower maximum flow rate 1.75 gpm @ 80 psi, 6.6 L/min @ 550 kPa
- Trim only for single handle Roman Tub Faucet with Hand Shower
- Temperature only controlled with handle
- Hot/cold indicator
- Rough-in Kit must be ordered to complete installation:
 - R3707, R3707-MF and R3707-PX for flexible rough-in.
- R3716, R3716-MF and R3716-PX for fixed rough-in.
 There are separate specification sheets on each rough-in kit, if more detail is required.
- Hand Shower includes double check valves for backflow prevention

NOTES

Rough-in must be installed so handle is on the left of the spout with the spout facing forward. Refer to M&I for more details. Spacing between hand shower and spout could be 5"-8" (127 mm - 203 mm).

WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes: or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.



COMPLETE VALVE COMPLIES WITH:

ASME A112.18.1 / CSA B125.1
Indicates ADA compliance to
ICC/ANSI A117.1 – Valve Only

